

Interchangeable Products

- RICE LAKE WEIGHING SYSTEMS
RL1260 page 178
- RICE LAKE WEIGHING SYSTEMS
RLPWM16 page 172
- HBM*
PW16 page 258

*Color code is different



Specifications

- Full Scale Output:**
2.0 mV/V
- Output Resistance:**
350 (± 3) ohms
- Input Resistance:**
415 (± 15) ohms
- Material/Finish:**
Anodized aluminum
- Temperature:**
Compensated range
14°F to 104°F (-10°C to 40°C)
Operating range
-40°F to 150°F (-40°C to 65°C)
- Safe Overload:**
150% of full scale at center loading point
- Rated Excitation:**
5-10 VDC (15 V maximum)
- Total Error:**
0.02% full scale
- Insulation Resistance:**
2,000 megohms
- Seal Type:**
Environmentally sealed, IP67
- Cable Length:**
10 ft (3.1 m)
- Cable Diameter:**
0.220 polyurethane jacket
- Cable Color Code:**
Green+ Excitation
Black.....- Excitation
Blue+ Sense
Brown- Sense
Red+ Signal
White- Signal

- Max Platform Size:**
24 in x 24 in
- Warranty:**
One-year limited warranty
- Approvals:**



Available Available
upon upon
request request

Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	C1	D	E	F	G	H
kg/mm									
50-635	188.00	52.00	35.00	142.00	5.5	62.3	50.00	5/16-18 UNC-2B	62.3
lb/in									
110.2-1,399.9	7.40	2.05	1.38	5.59	0.22	2.45	1.97	5/16-18 UNC-2B	2.45

Order Information

Load Rating	Part#	Est. Weight	Price
50 kg	40769	5 lb	Consult
75 kg	40770	5 lb	Consult
100 kg	40771	5 lb	Consult
200 kg	40772	5 lb	Consult
250 kg	40773	5 lb	Consult
300 kg	40774	5 lb	Consult
500 kg	40775	5 lb	Consult
635 kg	40776	5 lb	Consult

