

## Specifications

**Enclosure:**

NEMA Type 4, IP65

**Weight:**

0.98 lb (445 g)

**Keypad:**

On/Off, Zero (100%), Tare, Print, and two user-defined keys for the following functions: peak hold, high resolution, total, view total, net/gross, units switching

**Display:**

Six-digit 1.0 in (26.4 mm) LCD

**Units Displayed:**

Pounds, kilograms, tons, metric tons, kilonewtons

**Annunciators:**

Stable, COZ, low battery, peak, net, kg, kN, lb, M, ton, setpoint, function LEDs

**Power:**

Integral lithium ion battery  
Universal 115/230VAC, 50/60 Hz battery charger  
(NA plug included)

**Operating Time:**

Up to 24 hours of continuous use (15 minute auto-shutoff with non-use)

**Operating Temperature:**

-4° F to 140° F (-20° C to 60° C)

**RF Radio Link:**

2.4 GHz 802.15.4  
Communicates with 3460, 4260, 7300, 7000 & 7001

**RF Effective Range:**

Typically 100 or more feet (33 m)

**Connector:**

Four-pin Turck connector for charging and RS-232 communication

**Warranty:**

One-year limited warranty



## Standard Features

- Handheld RF remote display with six-digit 1.0 in (26.4 mm) LCD screen
- Membrane keypad for remote control functionality
- User definable function keys for added versatility
- Universal 115/230 VAC, 50/60 Hz battery charger (NA plug standard)
- Communicates with RF 4260, 7300, 7000 & 7001

## Part Number/Price

Part #	MSI Part #	Description	Price
139381	503208-0001	MSI-8000 RF remote display (requires ScaleCore™ equipped MSI-7300, MSI-4260, MSI-3460 and TranSend receivers)	Consult

## Options/Accessories

Part #	MSI Part #	Description	Price
149549	503486-0001	Universal 115/230 VAC 50/60 Hz (NA plug standard) battery charger for MSI-8000 RF remote display	Consult
149550	503486-0002	Universal 115/230 VAC 50/60 Hz (EC plug standard) battery charger for MSI 8000 RF remote display	Consult
150964	503489-0001	DB9 female serial interface cable for MSI-8000 RF remote display	Consult
151095	503506-0001	Audible alarm	Consult
182233		12V car charger adapter for MSI-8000	Consult

## Dimensions

A	8.00 in (203 mm)	C	3.85 in (98 mm)
B	3.85 in (98 mm)	D	1.37 in (35 mm)

