



# Model 9300 Weight Indicator

- 6-digit display
- 60,000 display graduations
- Powers up to 8 load cells
- 15 Updates/second typical
- NEMA 4 stainless steel washdown enclosure
- Selectable primary/secondary units  
lb, kg, ounces, short tons, metric tons,  
grams or none.
- 2 Independent serial  
communications ports:  
(1) full duplex, (1) unidirectional or  
active 20 mA current loop
- Full front-panel digital calibration  
& configuration
- Three-stage digital filtering
- CE Marked



## SPECIFICATIONS

### ELECTRICAL

Excitation Voltage ..... 10 ±0.5 VDC,  
8 x 350Ω load cells or  
16 x 700Ω load cells

### PERFORMANCE

Maximum Display Counts ..... 100,000  
Analog Signal Input Range ..... 0.6 mV/V - 4.5 mV/V  
Sensitivity ..... 0.3µV/graduation min.  
Measurement Rate ..... 15 measurements/second

### ENVIRONMENTAL

Operating Temperature ..... 14 to 122°F  
-10 to 50°C

### POWER

AC Power ..... 115 OR 230 VAC  
50-60 HZ

### MECHANICAL

Weight ..... 6.4 lb (2.9 kg)  
Enclosure ..... NEMA 4X/IP66  
stainless steel  
Enclosure Size ..... 9.5 in x 6 in x 2.75 in  
Display ..... 6 digit LED

## OPTIONS

Analog output: selectable 0-10V,  
4-20 mA

Panel mount kit

Please specify if CE mark is required