

# 1260S

Aluminum, NTEP Certified 1:10,000 Class III Single Cell, IP66



## Interchangeable Products

RICE LAKE WEIGHING SYSTEMS

**RL1260** ..... page 178

VPG TEDEA-HUNTLEIGH®

**1260** ..... page 353

## Specifications

**Full Scale Output:**  
2.0 mV/V

**Output Resistance:**  
350 (± 3) ohms

**Input Resistance:**  
415 (± 15) ohms

**Material/Finish:**  
Anodized aluminum

**Temperature:**  
Compensated range  
14°F to 104°F (-10°C to 40°C)  
Operating range  
-40°F to 150°F (-40°C to 65°C)

**Safe Overload:**  
150% of full scale at center loading point

**Rated Excitation:**  
5-10 VDC (15 V maximum)

**Total Error:**  
0.02% full scale

**Insulation Resistance:**  
2,000 megohms

**Seal Type:**  
Environmentally sealed, IP66

**Cable Length:**  
10 ft (3.1 m)

**Cable Diameter:**  
0.220 polyurethane jacket

**Cable Color Code:**  
Green ..... + Excitation  
Black ..... - Excitation  
Blue ..... + Sense  
Brown ..... - Sense  
Red ..... + Signal  
White ..... - Signal

**Max Platform Size:**  
24 in x 24 in

**Warranty:**  
One-year limited warranty

**Approvals:**



## Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	D	E	F	G	H	I	J	K	L	M
kg/mm													
75-635	52.00	16.00	62.3	52.00	16.00	52.3	63.00	50.00	35.00	107.00	35.00	5.5	188.00
lb/in													
165.4-1,399.9	2.04	0.62	2.45	2.04	0.62	2.05	2.48	1.96	1.37	4.21	1.37	0.21	7.40

## Order Information

Load Rating		Part #	Est. Weight	Price
75 kg	165.4 lb	<b>76395</b>	5 lb	Consult
100 kg	220.5 lb	<b>76396</b>	5 lb	Consult
150 kg	330.75 lb	<b>76397</b>	5 lb	Consult
200 kg	440.9 lb	<b>76398</b>	5 lb	Consult
250 kg	551.2 lb	<b>76399</b>	5 lb	Consult
300 kg	661.4 lb	<b>76400</b>	5 lb	Consult
500 kg	1,102.3 lb	<b>76401</b>	5 lb	Consult
635 kg	1,399.9 lb	<b>76402</b>	5 lb	Consult

